

Ausladung und Tragfähigkeit




Radius and capacity / Portée et charge / Sbraccio e portata / Alcances y cargas / Alcance e capacidade de carga

	m/kg		m/kg																			
			16,0	18,0	20,0	21,0	22,0	23,0	24,0	25,0	25,5	26,0	27,0	28,0	29,0	30,0	31,0	32,0	33,0	34,0	35,0	36,0
36,0	3,3 19,40 2500		2500	2500	2410	2280	2160	2050	1950	1860	1810	1770	1690	1620	1560	1490	1440	1380	1330	1290	1240	1200
33,0	3,3 20,18 2500		2500	2500	2500	2390	2260	2150	2040	1950	1900	1860	1780	1700	1630	1570	1510	1450	1400			
30,0	3,3 21,04 2500		2500	2500	2500	2500	2370	2250	2140	2040	2000	1950	1870	1790	1720	1650						
25,5	3,3 21,95 2500		2500	2500	2500	2500	2490	2370	2250	2150	2100											
	m/kg		m/kg																			
			13,0	14,0	16,0	18,0	20,0	23,0	24,0	25,0	25,5	26,0	27,0	28,0	29,0	30,0	31,0	32,0	33,0	34,0	35,0	36,0
36,0	3,3 22,56 2000		2000	2000	2000	2000	2000	1950	1850	1760	1720	1680	1600	1530	1460	1400	1340	1290	1230	1190	1140	1100
33,0	3,3 23,46 2000		2000	2000	2000	2000	2000	2000	1950	1850	1800	1760	1680	1600	1530	1470	1410	1350	1300			
30,0	3,3 24,45 2000		2000	2000	2000	2000	2000	2000	2000	1950	1900	1850	1770	1690	1620	1550						
25,5	3,3 25,50 2000		2000	2000	2000	2000	2000	2000	2000	2000	2000											
	m/kg		m/kg																			
			13,0	14,0	16,0	18,0	20,0	23,0	24,0	25,0	25,5	26,0	27,0	28,0	29,0	30,0	31,0	32,0	33,0	34,0	35,0	36,0
36,0	3,3 12,77 4000		3910	3580	3040	2630	2320	1950	1850	1760	1710	1670	1600	1520	1460	1400	1340	1280	1230	1190	1140	1100
33,0	3,3 13,25 4000		4000	3740	3180	2760	2430	2050	1940	1850	1800	1760	1680	1600	1530	1470	1410	1350	1300			
30,0	3,3 13,79 4000		4000	3930	3340	2900	2550	2150	2050	1950	1900	1850	1770	1690	1620	1550						
25,5	3,3 14,36 4000		4000	4000	3510	3050	2690	2270	2150	2050	2000											

m	m/kg		Auslegersteilstellung 30° / Elevated jib 30° / Flèche inclinée 30° Braccio inclinato a 30° / Pluma inclinada 30° / Lança inclinada 30°											
			16,0	18,0	20,0	22,3	23,0	24,0	25,0	26,0	26,2	27,0	28,0	28,7
36,0	3,0 15,91 2500		2480	2160	1900	1670	1610	1530	1450	1390	1370	1320	1270	1220
33,0	3,0 16,67 2500		2500	2280	2010	1770	1700	1620	1540	1470	1460	1400	1340	1300
30,0	3,0 17,51 2500		2500	2420	2140	1880	1810	1720	1640	1560	1550			
25,5	3,0 18,45 2500		2500	2500	2270	2000								


Antriebe

Driving units / Mécanismes d'entraînement / Azionamenti / Mecanismos / Mecanismos

	U/min. 0 ↔ 0,9 sl./min tr./min	3,0 kW EDC
	20,0 / 40,0 m/min	1,3 / 2,3 kW
	25,0 m/min	2 x 1,3 kW
	0 45°, ca. 60 sec.	1,5 kW

BGL	 C.0.08.0045	 +  C.0.08.0045
-----	---	---

	400 V	Hz	kVA
50,0 m	4 x 6 mm ² KL		25,0 KL
77,0 m	4 x 6 mm ² FU	50	20,0 FU

	Stufe / Step / Cran		m/min
	Marcia / Velocidad	kg	
11,0 kW KL		1 2500	5,0
		2 2500	20,0
		3 1300	40,0
		1 2000	5,0
		2 4000	2,5
		3 2000	20,0
11,0 kW FU		1 2500	4,0
		2 2500	20,0
		3 1300	38,0
		4 1000	50,0
		1 2000	4,0
		2 4000	2,0
		3 2000	20,0
		4 4000	10,0
		3 1300	38,0
		4 2600	19,0